


BAKHITA


Studio Eurolinea Design, 2014



0,32m³ - 19,6 kg
50x65x99cm
4 pcs [carton]

Stackable on floor [5pcs]
Impilabile a terra [5pz]

Twin-material techno-polymer chair.
Sedia bi-materiale in tecnopolimero.



FIRE RETARDANT

IGN Versions follows UNI 9177 certification in terms of Fire Resistance, Fire Reaction Class 1.
Versioni IGN prodotto Omologato con Classe di Reazione al fuoco 1, UNI 9177.




PERFORMED TEST

1. Safety requirements EN 16139:2013+AC:2013
2. Information for use EN 16139:2013+AC:2013
3. Seat and back static load test EN 1728:2012+AC:2013
4. Vertical load on back rest EN 1728:2012+AC:2013
5. Seat and back fatigue test EN 1728:2012+AC:2013
6. Seat front edge durability test EN 1728:2012+AC:2013
7. Leg forward static load test EN 1728:2012+AC:2013
8. Leg sideways static load test EN 1728:2012+AC:2013
9. Seat impact test EN 1728:2012+AC:2013
10. Back impact test EN 1728:2012+AC:2013
11. Stability - EN 1022:2005



BAKHITA B


Studio Eurolinea Design, 2014



0,38m³ - 22 kg
59x65x99cm
4 pcs [carton]

Stackable on floor [5pcs]
Impilabile a terra [5pz]

Twin-material techno-polymer chair with integrated armrests.
Sedia bi-materiale in tecnopolimero con braccioli integrati.



FIRE RETARDANT

IGN Versions follows UNI 9177 certification in terms of Fire Resistance, Fire Reaction Class 1.
Versioni IGN prodotto Omologato con Classe di Reazione al fuoco 1, UNI 9177.



PERFORMED TEST UNI EN 16139:2013


Furniture Requirements - Resistance, durability and safety

1. Safety requirements UNI EN 16139:2013 + EC 1-2013
2. Stability UNI EN 16139:2013 + EC 1-2013
3. Seat and back static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
4. Seat forward static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
5. Vertical load on backrest UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
6. Arm sideways static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
7. Arm downwards static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
8. Arm upwards static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
9. Seat and back fatigue test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
10. Seat front edge durability test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
11. Arm fatigue test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
12. Leg forward static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
13. Leg sideways static load test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
14. Seat impact test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
15. Back impact test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
16. Armrest impact test UNI EN 16139:2013 + EC 1-2013 + UNI EN 1728:2012 + EC 1-2013 + EC 2-2013 + EC 3-2015
17. Information for use UNI EN 16139:2013 + EC 1-2013
18. Dimensional requirements (visitors office chairs) UNI EN 16139:2013 + EC 1-2013



BAKHITA 66

Studio Eurolinea Design, 2014



0,37 m³ - 23 kg
63x49x118cm
4 pcs [carton]

Stackable on floor [8pcs]
Impilabile a terra [8pz]



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

Co-injected metal-polymer stackable stool.
Sgabello impilabile in co-iniezione polimero-metallo.



FIRE RETARDANT

IGN Versions follows UNI 9177 certification in terms of Fire Resistance, Fire Reaction Class 1.
Versioni IGN prodotto Omologato con Classe di Reazione al fuoco 1, UNI 9177.



ACCESSORIES

CUSHION | CUSCINO

Bakhita cuscion, complete with white under seat cover.
Cuscino Bakhita, completo di sottoscocca bianco.



CUSHION AVAILABLE FABRICS

- [B] Blazer Fabric
- [DK] Kvadrat Fabric - Steelcut 3
- [DK] Kvadrat Fabric - Remix 3
- [E] Synthetic Leather Aurea
- [K] King Fabric
- [MG] Maglia Fabric
- [SX] Silvertex Fabric

[TC] COM Fabric


Cushion fabric required 4pcs: Lin Mtrs 1 (h 1,40)

White flexible polyurethane foam, density 30kg/m³, flame retardant according to the method:
UNI 9175 - UNI 9175 / FA1, Class 1IM.

Poliuretano espanso flessibile di colore bianco, densità 30kg/m³, ignifugo secondo il metodo:
UNI 9175 - UNI 9175/FA1, Classe 1IM.

BAKHITA 76

Studio Eurolinea Design, 2014



0,37 m³ - 24 kg
63x49x118cm
4 pcs [carton]

Stackable on floor [8pcs]
Impilabile a terra [8pz]



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

Co-injected metal-polymer stackable stool.
Sgabellu impilabile in co-iniezione polimero-metallo.



FIRE RETARDANT

IGN Versions follows UNI 9177 certification in terms of Fire Resistance, Fire Reaction Class 1.
Versioni IGN prodotto Omologato con Classe di Reazione al fuoco 1, UNI 9177.



PERFORMED TEST

1. Safety requirements EN 16139:2013+AC:2013
2. Information for use EN 16139:2013+AC:2013
3. Seat and back static load test and seat front edge static load test EN 1728:2012+AC:2013
4. Foot rest static load test EN 1728:2012+AC:2013
5. Seat and back fatigue test EN 1728:2012+AC:2013
6. Seat front edge durability test EN 1728:2012+AC:2013
7. Foot rest durability test EN 1728:2012+AC:2013
8. Leg forward static load test EN 1728:2012+AC:2013
9. Leg sideways static load test EN 1728:2012+AC:2013
10. Seat impact test EN 1728:2012+AC:2013
11. Back impact test EN 1728:2012+AC:2013
12. Stability - EN 1022:2005
13. Stability EN 1022:2023, clause 7.3

PERFORMED TEST

1. Backrest strength test - Static ANSI-BIFMA X5.1-2011/6
2. Stability test ANSI-BIFMA X5.1-2011/12
3. Seating durability test - Cyclic - ANSI-BIFMA X5.1-2011/11
4. Back durability test - Cyclic-Type II and III ANSI-BIFMA X5.1-2011/16
5. Arm durability test - cyclic ANSI-BIFMA X5.1 2011/21
6. Drop test - Dynamic - ANSI- BIFMA X5.1-2011/8
7. Arm strength test-Vertical-Static ANSI-BIFMA X5.1-2011/13
8. Arm strength - Horizontal-Static ANSI-BIFMA X5.1-2011/14
9. Leg strength test - Front application ANSI-BIFMA X5.1-2011/18
10. Leg strength test - Side application ANSI-BIFMA X5.1-2011/18



ACCESSORIES

CUSHION | CUSCINO

Bakhita cushion, complete with white under seat cover.
Cuscino Bakhita, completo di sottoscocca bianco.



CUSHION AVAILABLE FABRICS

- [DK] Kvadrat Fabric - Steelcut 2
- [DK] Kvadrat Fabric - Remix 2
- [E] Synthetic Leather Aurea
- [K] King Fabric
- [TF] Fenice Fabric

[TC] COM Fabric

Cushion fabric required 4pcs: Lin Mtrs 1 (h 1,40)

White flexible polyurethane foam, density 30kg/m³, flame retardant according to the method:
UNI 9175 - UNI 9175 / FA1, Class 1IM.

Poliuretano espanso flessibile di colore bianco, densità 30kg/m³, ignifugo secondo il metodo:
UNI 9175 - UNI 9175/FA1, Classe 1IM.

CONNECTING SYSTEM | GANCIO CONNESSIONE

Extensible chromed linking devices for in line disposal, complete with underseat cover.
Agganci estensibili cromati per disporre le sedute in linea, con sottoscocca integrato.



TROLLEY | CARRELLO (10pcs)

Trolley for 10 chairs model Bakhita, black painted.

Carrello per 10 sedie modello Bakhita, verniciato nero.



In all components, parts or materials used to make its products, be they plastic or metal, there are no dangerous substances within the certified limits of the following test methods reports:

In tutti i componenti, parti o materiali utilizzati per realizzare i prodotti, siano essi plastici o metallici, non sono presenti sostanze pericolose nei limiti certificati dei seguenti metodi e rapporti di prova:

Cadmium/Cadmio UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Lead/Piombo UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Mercury/Mercurio UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Arsenic/Arsenico UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Selenium/Selenio UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Chrome/Cromo VI CEI EN 62321:2009 Annex C
Diisobutil ftalato (DIBP) CPSC-CH-C1001-09.3:2010
Dibutil ftalato (DBP) CPSC-CH-C1001-09.3:2010
Benzilbutil ftalato (BBP) CPSC-CH-C1001-09.3:2010
Di-(2-etilesil) ftalato (DEHP) CPSC-CH-C1001-09.3:2010
Di-n-ottil ftalato (DNOP) CPSC-CH-C1001-09.3:2010
Diisononil ftalato (DINP) CPSC-CH-C1001-09.3:2010
Diisodecil ftalato (DIDP) CPSC-CH-C1001-09.3:2010
Dipentil ftalato (DPP) CPSC-CH-C1001-09.3:2010
Dimetossietil ftalato (DMEP) CPSC-CH-C1001-09.3:2010

Material "Plastomero/Elastomero" Report n. |Rapporto di prova n. 20205954-002

Material "Polipropilene FVR" Report n. |Rapporto di prova n. 20205954-003



BAKHITA COLLECTION

The tecnologia is complex, the result is simple: a comfortable and high quality lightweight stacking chair for indoor and outdoor purpose.

La tecnologia è complessa, il risultato semplice: una seduta di alta qualità, leggera, impilabile, confortevole, per interni ed esterni.

